


September 1998

The **LTC[®]1050** data sheet has been modified as shown below in **Bold**. For complete specifications, typical performance characteristics and applications information, please see the **LTC1050** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

ELECTRICAL CHARACTERISTICS

$V_S = \pm 5V$, T_A = Operating Temperature Range unless otherwise specified.

PARAMETER	CONDITIONS		LTC1050AM			LTC1050AC			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
Input Offset Current	$T_A = 25^\circ C$ (Note 5)	●		± 20	± 60 ± 300		± 20	± 60 ± 150	pA pA
Input Bias Current	$T_A = 25^\circ C$ (Note 5)	●		± 10	± 30 ± 2000		± 10	± 30 ± 100	pA pA

PARAMETER	CONDITIONS		LTC1050M			LTC1050C			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
Input Offset Current	$T_A = 25^\circ C$ (Note 5)	●		± 20	± 100 ± 300		± 20	± 125 ± 200	pA pA
Input Bias Current	$T_A = 25^\circ C$ (Note 5)	●		± 10	± 50 ± 2000		± 10	± 75 ± 150	pA pA

The ● denotes the specifications which apply over the full operating temperature range.

Note 5: At $T_A \leq 0^\circ C$ these parameters are guaranteed by design and not tested.

For further information regarding this specification notice contact:

Linear Technology Corporation
1630 McCarthy Blvd.
Milpitas, California 95035-7417
Attn: Product Marketing Manager
Phone: (408) 432-1900