



The specifications for the **LT<sup>®</sup>1107IS8** over the  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$  temperature range are the same as those shown on the existing LT1107 data sheet for the Military Temperature range version. Addition of Industrial grade part is shown in **bold** in the following list. For complete specifications, typical performance curves and applications information, please see the **LT1107** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

## PACKAGE/ORDER INFORMATION

<p style="text-align: center;">TOP VIEW</p>  <p>J8 PACKAGE 8-LEAD Cerdip</p> <p>N8 PACKAGE 8-LEAD PDIP</p> <p>S8 PACKAGE 8-LEAD PLASTIC SO</p> <p>* FIXED VERSIONS</p>	<p>ORDER PART NUMBER</p> <p>LT1107CN8 LT1107CN8-5 LT1107CN8-12 LT1107MJ8 LT1107MJ8-5 LT1107MJ8-12 LT1107CS8 LT1107CS8-5 LT1107CS8-12 <b>LT1107IS8</b></p> <p>S8 PART MARKING</p> <p>1107 11075 110712 <b>1107I</b></p>
---	--

## ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range

LT1107C .....  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$

**LT1107I** .....  **$-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$**

LT1107M .....  $-65^{\circ}\text{C}$  to  $150^{\circ}\text{C}$

For further information regarding this specification notice contact:

Linear Technology Corporation  
 1630 McCarthy Blvd.  
 Milpitas, California 95035-7417  
 Attn: Product Marketing Manager  
 Phone: (408) 432-1900