

January 1997

## DESCRIPTION

The SSI 32P4903B is a high performance BiCMOS read channel IC that provides all of the functions needed to implement an entire Partial Response Class 4 (PR4) read channel for zoned recording hard disk drive systems with data rates from 24 to 90 Mbit/s.

Functional blocks include AGC, programmable filter, adaptive transversal filter, Viterbi qualifier, 8,9 GCR ENDEC, data synchronizer, time base generator, and 4-burst servo capture.

Programmable functions such as data rate, filter cutoff, filter boost, etc., are controlled by writing to the Serial Port Registers so no external component changes are required to change zones.

The SSI 32P4903B utilizes an advanced BiCMOS process technology along with advanced circuit design techniques which result in high performance devices with low power consumption. The part requires a single +5 V power supply.

## FEATURES

### GENERAL

- Register programmable data rates from 24 to 90 Mbit/s
- Sampled data read channel with Viterbi qualification
- Programmable filter for PR4 equalization
- 3-tap transversal filter for adaptive PR4 equalization
- 8/9 GCR ENDEC
- Data scrambler/descrambler
- Programmable write precompensation
- Low operating power (0.75 W typical at 5 V)
- Register programmable power management
- Dual-bit and byte wide bi-directional NRZ data interfaces
- Thermal asperity detection and suppression
- Serial interface port for access to internal program storage registers
- Single power supply (5 V  $\pm 10\%$ )
- Small footprint 80-Lead TQFP package

### AUTOMATIC GAIN CONTROL

- Dual mode AGC, analog during acquisition, sampled during data reads
- Separate AGC level storage pins for data and servo
- Dual rate attack and decay charge pump for rapid AGC recovery
- Programmable, symmetric, charge pump currents for data reads
- Charge pump currents track programmable data rate during data reads
- Low drift AGC hold circuitry
- Low-Z input switch
- AGC hold, fast recovery, and AGC input impedance control signals
- Wide bandwidth, precision full-wave rectifier

### FILTER/EQUALIZER

- Programmable, 7-pole, continuous time filter provides:
  - Channel filter and pulse slimming equalization for equalization to PR4
  - Programmable cutoff frequency, 3 to 24 MHz
  - Programmable boost /equalization, 0 to 13 dB
  - $\pm 0.6$  ns group delay variation from 0.2  $f_c$  to  $f_c$ , with  $f_c = 24$  MHz
  - Minimizes size and power
  - Low-Z input switch
- 3-tap self adapting transversal filter for fine equalization to PR4
- No external components required

### PULSE QUALIFICATION

- Sampled Viterbi qualification of signal equalized to PR4
- Dual level pulse qualifier for servo reads

### TIME BASE GENERATOR

- Less than 1% frequency resolution
- Up to 101 MHz frequency output
- Independent M and N divide-by registers
- No active external components required

## BLOCK DIAGRAM

