

TMS320C6x Thermal Design Considerations

APPLICATION REPORT: SPRA432

David Bell

*Digital Signal Processing Solutions
April 1998*



IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain application using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

TRADEMARKS

TI is a trademark of Texas Instruments Incorporated.

Other brands and names are the property of their respective owners.

CONTACT INFORMATION

US TMS320 HOTLINE	(281) 274-2320
US TMS320 FAX	(281) 274-2324
US TMS320 BBS	(281) 274-2323
US TMS320 email	dsph@ti.com

Contents

Abstract	9
Product Support.....	9
Related Documentation.....	9
World Wide Web	9
Email.....	9
Design Problem	9
Solution	9
Thermal Considerations	11
Thermal Analysis and Heat Sink Selection	11
Example 1:.....	12
Example 2:.....	13

Figures

Figure 1. Thermal Model Used for Heat Flow Analysis	11
Figure 2. Heat Sink Performance Plot	13
Figure 3. Heat Sink Performance Plot	14

TMS320C6x Thermal Design Considerations

Abstract

This document discusses thermal analysis and heat sink selection for the Texas Instruments (TI™) TMS320C6x digital signal processor (DSP). A simplified approach is offered to select a heat sink that matches a particular operating environment. Examples are included to demonstrate the method for selecting a heat sink for a typical design.

Product Support

Related Documentation

The following list specifies product names, part numbers, and literature numbers of corresponding TI documentation.

- ❑ *Document title*, Literature number SXXX0000
- ❑ *Document title*, Literature number SXXX0000

World Wide Web

Our World Wide Web site at **www.ti.com** contains the most up to date product information, revisions, and additions. Users registering with TI&ME can build custom information pages and receive new product updates automatically via email.

Email

For technical issues or clarification on switching products, please send a detailed email to **dsph@ti.com**. Questions receive prompt attention and are usually answered within one business day.



Design Problem

Thermal analysis and heat sink selection for the TMS320C6x.

Solution

Like most high-performance processors, the 'C6x dissipates some thermal energy during normal operation. The high level of integration, high clock frequency, and large on-chip memory arrays have an increased effect on the silicon junction temperature (T_j) compared with a lower performance DSP. To ensure proper operation and device reliability, the silicon junction temperature must not exceed maximum junction temperature (related to maximum case temperature $T_{C_{max}}$). Under normal operating conditions, system level thermal management is needed to assist with dissipating the heat away from the chip package. A passive heat sink provides a reliable and cost effective method for removing the excess heat. The size and shape of the heat sink depend on the operating conditions of the 'C6x device and the characteristics of the system within which it operates.

Most of the current consumed by CMOS devices is Alternating Current (AC), which charges and discharges the capacitance of internal nodes, pins, and external pin loads. The current flowing through the 'C6x causes the temperature of the silicon die to rise. To maintain device reliability and proper operation, the junction temperature must not exceed the maximum specified junction temperature. As the heat is transferred from the die to the package, the case temperature of the package also rises. The junction-to-case thermal resistance $R_{\theta jc}$, together with the maximum junction temperature, are parameters that determine the maximum case temperature $T_{C_{max}}$. Because of these factors, the specification of temperature is given in terms of $T_{C_{max}}$ in the Thermal Analysis section of this document.

The heat typically flows from the case to the surrounding air up through the heat sink and down through the pins and the board. The heat dissipation through the board material largely depends on the number of power and ground layers inside the board. The portion of the power that is dissipated by the heat sink must first propagate through the case-sink joint. The thermal resistance of case to sink joint can vary depending on the type of joint used, such as thermal epoxy or double-sided adhesive pads. The rate at which the heat is transferred from the sink to the ambient air depends largely on the velocity of the air at the heat sink. The heat flow from the sink rises with the speed of the airflow.

The examples in this section present a method for first order approximation of the size of the heat sink needed to keep the maximum case temperature from exceeding $T_{C_{max}}$ during maximum system operating conditions. Following heat sink installation, the actual case temperature should be measured to verify that it doesn't exceed the $T_{C_{max}}$ value.

Heat transfer analysis can be a complex task depending on the degree of accuracy required in the modeling of system components. A number of computational fluid dynamics and heat transfer tools are available to provide highly accurate results. Experimental methods can be used as well for analyzing heat flow.

This document uses a simplified approach to select a heat sink that matches a particular operating environment. The driving parameter in determining the heat flow is the maximum case temperature that must stay below $T_{C_{max}}$ at all times during device operation. The system parameters that have first order effect on the case temperature are

- ☐ Average device power dissipation
- ☐ Ambient air temperature
- ☐ Air approach velocity

The choice of the heat sink largely depends on those factors, as shown in the following examples. Other factors that can affect heat dissipation include board design/materials and the case to sink attachment method. The relatively long Time Constant of the case/sink combination (around 2 minutes) can effectively smooth out any power peaks that may occur. To validate proper operation of the heat sink, a small hole should be drilled in the center of the sink to place a miniature thermocouple directly on the case (center top surface) to measure the actual case temperature under system's maximum expected operating conditions.

Thermal Considerations

'C6x device operating conditions that can affect power dissipation:

- ☐ Operating frequency
- ☐ Use of power-down (idle) modes
- ☐ Amount of on-chip activity
- ☐ Number of functional units exercised every cycle
- ☐ Frequency of the internal data memory accesses

- ❑ Frequency of the internal program memory accesses
- ❑ Activity level of on-chip peripherals (DMAs, Serial Ports, etc.)
- ❑ Rate at which data is being driven on and off the chip


System considerations for choosing a heat sink:

- ❑ Air flow rate over the board housing the 'C6x
- ❑ ambient air temperature
- ❑ Area / type of joint between package and the heat sink
- ❑ Board design and layout

Thermal Analysis and Heat Sink Selection

The following examples demonstrate the method for selecting a heat sink for a typical design. Figure 1 shows the thermal model of the 'C6x mounting.

Figure 1. Thermal Model Used for Heat Flow Analysis



Example 1:

- Specify operating conditions (this system reflects a typical PC operating environment)

$P_a = 4.2 \text{ W}$	average power dissipated by the case
$T_{a_{\max}} = 40 \text{ }^{\circ}\text{C}$	ambient air temperature
$V_{a_{\min}} = 85 \text{ LFM}$	air approach velocity (linear feet per minute)
$h_{\max} = 9\text{mm}$	height limit for the heat sink (system requirement)
$R_{\theta_{cs}} = 0.5 \text{ }^{\circ}\text{C/W}$	case to sink thermal resistance (using thermal epoxy)
$T_{C_{\max}} = 90 \text{ }^{\circ}\text{C}$	case temperature

- Estimate the total power that needs to be dissipated by the heat sink, P_s .

$$P_s = P_a - 1\text{W} \quad (\text{assume } 1\text{W dissipation through the board})$$

$$P_s = 4.2 - 1 = 3.2 \text{ W}$$

- Compute the maximum heat sink to air thermal resistance $R_{\theta_{sa}}$ that will maintain the case temperature below $T_{C_{\max}}$ for the operating conditions specified above.

$$R_{\theta_{sa}} + R_{\theta_{cs}} = (T_c - T_a) / P_s$$

$$R_{\theta_{sa}} = \{(T_c - T_a) / P_s\} - R_{\theta_{cs}}$$


$$R_{\theta_{sa}} = \{(90 - 40) / 3.2\} - 0.5$$

$$R_{\theta_{sa}} = 15.1 \text{ }^{\circ}\text{C/W}$$

- Choose the heat sink based on the computed maximum sink to air resistance $R_{\theta_{sa}}$ and the minimum air approach velocity inside the enclosure. The heat sink performance plot below verifies that at 85 LFM minimum air velocity, the sink to air thermal resistance will indeed stay at or below the R_{sa} value of $15.1 \text{ }^{\circ}\text{C/W}$ that is required to maintain the case temperature below $T_{C_{\max}}$ for the listed operating conditions. Actual experimental measurement of the case temperature should be performed next to verify heat sink performance. Figure 2 gives the performance plot of a heat sink that would satisfy the requirements of the system in Example 1.



Figure 2. Heat Sink Performance Plot

**Example 2:**
☐ Specify operating conditions

$P_a = 6.9 \text{ W}$	average power dissipated by the case
$T_{a_{\max}} = 55 \text{ }^\circ\text{C}$	ambient air temperature
$V_{a_{\min}} = 140 \text{ LFM}$	air approach velocity (linear feet per minute)
$h_{\max} = 17\text{mm}$	height limit for the heat sink (system requirement)
$R\theta_{cs} = 0.2 \text{ }^\circ\text{C/W}$	case to sink thermal resistance (using thermal grease)
$T_{c_{\max}} = 90 \text{ }^\circ\text{C}$	case temperature

☐ Estimate the total power that needs to be dissipated by the heat sink, P_s

$$P_s = P_a - 2\text{W} \quad (\text{assume } 2\text{W dissipation through the board})$$

$$P_s = 6.9 - 2 = 4.9 \text{ W}$$

☐ Compute the maximum heat sink to air thermal resistance $R\theta_{sa}$ that will maintain the case temperature below $T_{c_{\max}}$ for the operating conditions specified above.

$$R\theta_{sa} + R\theta_{cs} = (T_c - T_a) / P_s$$

$$R\theta_{sa} = \{(T_c - T_a) / P_s\} - R\theta_{cs}$$

$$R\theta_{sa} = \{(90 - 55) / 4.9\} - 0.2$$

$$R\theta_{sa} = 6.9 \text{ }^\circ\text{C/W}$$

- ❑ Choose the heat sink based on the computed sink to air resistance $R_{\theta sa}$ and the minimum air approach velocity inside the enclosure. The heat sink performance plot below verifies that at 140 LFM minimum air velocity, the sink to air thermal resistance will indeed stay at or below the R_{sa} value of 6.9 °C/W that is required to maintain the case temperature below $T_{c_{max}}$ for the listed operating conditions. Actual experimental measurement of the case temperature should be performed next to verify heat sink performance. Figure 3 gives the performance plot of a heat sink satisfying the requirements of the system in Example 2.

Figure 3. Heat Sink Performance Plot

